



# PERFORMANCE FIRE RETARDANT FOAM

# ANECHOIC WEDGES

Sound Absorbing & Noise Blocking Products

## PFRF - FIRE RETARDANT FOAM

<b>Size:</b>	24" x 48" and 48" x 48"
<b>Thickness:</b>	1", 1.5", 2", 3", 4"
<b>Density:</b>	2 lb / cubic foot
<b>Flammability:</b>	Class One
<b>Flame Spread:</b>	10*
<b>Smoke Density:</b>	50*
<b>Colors:</b>	Natural White Paint and Hypalon Color available
<ul style="list-style-type: none"> <li>▶ Welding Areas</li> <li>▶ Churches &amp; Schools</li> <li>▶ Generator Plants</li> <li>▶ High Temperatures</li> </ul>	

Frequency (Hz)	125	250	500	1K	2K	4K	NRC
2" PFRF-AW	.03	.31	.81	1.02	1.01	.96	.80
3" PFRF-AW	.13	.74	1.26	1.18	1.12	1.03	1.10
4" PFRF-AW	.33	1.12	1.32	1.39	1.19	1.12	1.26

## SOUND [ISOLATION] COMPANY

2900 WESTINGHOUSE BLVD. SUITE 106  
 CHARLOTTE, NC 28273  
 704 / 504 / 1127 PH  
 704 / 504 / 1115 FX  
 888 / 666 / 5090 TOLL FREE  
 WWW.SOUNDISOLATIONCOMPANY.COM

**Call now to order your sound  
 absorbing products. (888) 666-5090**