



PERFORMANCE FIRE RETARDANT FOAM

MAX WEDGE DESIGN

Sound Absorbing & Noise Blocking Products

PFRF - ACOUSTIC MELAMINE

| | | | |
|----------------------|---|--------------------|--------------------------|
| Size: | 12" x 12" | | |
| Thickness: | 6" and 8" available | | |
| Density: | 0.7 lb / cubic foot | | |
| Flammability: | Class One | | |
| Flame Spread: | 10 | | |
| Smoke Density | 50 | | |
| Colors: | Natural White, Painted and Hypalon Colors | | |
| Applications: | ▶ Welding Areas | ▶ Generator Plants | |
| | ▶ Schools | ▶ Churches | ▶ High Temperature Areas |

SOUND [ISOLATION] COMPANY

2900 WESTINGHOUSE BLVD. SUITE 106
 CHARLOTTE, NC 28273
 704 / 504 / 1127 PH
 704 / 504 / 115 FX
 888 / 666 / 5090 TOLL FREE
 WWW.SOUNDISOLATIONCOMPANY.COM

| Frequency (Hz) | 125 | 250 | 500 | 1K | 2K | 4K | NRC |
|----------------|-----|------|------|------|------|------|------|
| PFRF-MW - 6" | .22 | 1.07 | 1.27 | 1.34 | 1.27 | 1.15 | 1.26 |
| PFRF-MW - 8" | .39 | 1.05 | 1.44 | 1.38 | 1.33 | 1.19 | 1.33 |

**Call now to order your sound
 absorbing products. (888) 666-5090**